

Installation Verticale										
Modèle	Capacité [L]	Gamme	Qelec [kWh]	Profil de charge	Alimentation	V40 [L]	η _{wh}	**Pertes statiques Q _{pr} [W/m² à 65°C]	*Production d'eau à 40°C [L]	L _{wa} [dB]
Ø470 VERT	50	THER	6,665	M	en continu	65	36,1%	0,79	nc	15
		STEFA/ACC	6,679	M		65	36,0%	0,72	nc	
	75	THER	6,688	M	en continu	90	36,0%	0,99	136	
		STEFA/ACC	6,550	M		85	36,6%	0,96	129	
Ø505 VERT	100	TICR	12,003	L	en continu	143	37,0%	1,31	176	
		STEFA	12,883	L		148	37,0%	1,31	180	
	150	THER	6,689	M	nocturne	222	36,0%	1,75	276	
		STEFA	6,689	M		237	36,0%	1,75	277	
	200	THER	12,883	L	nocturne	251	37,0%	2,15	359	
		STEFA	12,883	L		336	37,0%	2,15	372	
Ø530 VERT	100	THER	12,502	L	en continu	143	37,9%	1,06	176	
		HPC/ZEN/STEFA/ACC	12,442	L		148	38,0%	1,06	180	
	150	THER	6,601	M	nocturne	237	36,4%	1,35	276	
		HPC/ZEN/STEFA	6,578	M		222	36,5%	1,35	277	
	200	THER	12,612	L		351	37,6%	1,76	359	
		HPC/ZEN/STEFA	12,506	L		336	37,9%	1,76	372	
Ø560 VERT	100	THER	12,840	L	en continu	145	37,1%	1,03	177	
		HPC/QUIE/STEFA	12,792	L		140	37,2%	1,05/1,03*	176/172*	
	150	THER	6,681	M	nocturne	220	36,0%	1,48	276	
		HPC/QUIE/STEFA	6,669	M		230	36,1%	1,48/1,41*	271	
	200	THER	12,865	L		334	37,0%	1,73	370	
		HPC/QUIE/STEFA	12,766	L		332	37,3%	1,73	372	
	250	STEFA	12,821	L		nocturne	317	37,1%	1,97	455
	Installation Horizontale									
Ø505 HORB	75	THER	6,683	M	en continu	69	36,0%	nc	nc	15
Ø560 HORB	100	STEFA	6,353	M	en continu	121	37,5%	1,65	165	
		THER	6,246	M		108	38,0%	1,65	165	
	150	STEFA	12,798	L		196	37,2%	2,25	231	
		THER	12,552	L		177	37,8%	2,25	231	
	200	STEFA	13,126	L		231	37,0%	2,68	318	
		THER	13,126	L		197	37,0%	2,68	318	
Ø505 HORD	75	THER	6,531	M	en continu	96	36,7%	nc	nc	
Ø530 HORD	100	THER	6,687	M	en continu	158	36,0%	1,33	178	
	150	THER	12,882	L		222	37,0%	1,65	279	
	200	THER	12,882	L		301	37,0%	1,97	365	
Ø570 HORD	100	THER	6,687	M	en continu	160	36,0%	1,32	187	
	150	THER	12,882	L		263	37,0%	1,68	281	
	200	THER	12,882	L		303	37,0%	2,02	367	
Installation Sur socle										
Ø570 STABLE	200	THER	12,883	L	nocturne	330	37,1%	1,98	356	15
		HPC/STEFA	12,883	L		333	37,0%	1,98	349	
	250	THER	12,883	L		373	37,0%	2,36	469	
		STEFA	12,883	L		370	37,0%	2,36	460	
	300	THER	12,883	L		473	37,0%	2,61	525	
		STEFA	12,883	L		473	37,0%	2,61	515	
	250	HPC	12,879	L	nocturne	423	37,0%	2,17	458	
	270	HPC	12,667	L		430	37,5%	2,3	505	
	300	HPC	12,808	L		524	37,2%	2,45	563	
	300	QUIE/ZEN	12,883	L		473	37,0%	2,61	525	

* Valeur pour gamme HPC/PTEC (Ø560)

** Valeur selon le Cahier de charges LCIE 105-14D

nc = non concerné